



Epson Stylus Pro 4900

A combination of remote proofing capabilities, fast print speeds, high levels of automation and a super-wide colour gamut make the Epson Stylus Pro 4900 a highly productive workhorse for the small office or studio environment.

This compact 17-inch production printer sets new standards in colour precision for pre-press, packaging, design, commercial photographs and fine art reproduction. Achieving 98% PANTONE®* coverage, the Stylus Pro 4900 boasts outstanding colour consistency and accurate colour matching, and Epson's 11-colour UltraChrome HDR inks, incorporating auto selection of photo and matte black inks, and Advanced-TFP print head guarantee a professional finish every time.

The Stylus Pro 4900's automatic colour certification and calibration produces high-quality remote proofs. The optional inline SpectroProofer ensures consistent, repeatable colour accuracy when using different media, rapidly measuring control strips and colour charts when creating ICC profiles and print verification results.

With production speeds of up to 30m² per hour and minimal maintenance requirements, the Stylus Pro 4900 boosts studio productivity. The high-capacity front-loading cassette makes inserting paper easy, and automated paper changing means no time is wasted switching between cut sheet and roll paper. The printer switches automatically between pre-installed photo and matte black inks, and all inks come in high-capacity cartridges for less frequent changes and better value.

The Stylus Pro 4900 can print on a range of media up to 1.5mm thick, including thick photo or presentation matte board, canvas and fine art paper – and paper paths include cassette, top and front manual board feed or roll.

KEY FEATURES

- Wide colour gamut of up to 98% PANTONE® coverage
- Automatic colour certification and calibration for consistent colour matching
- Automated production with optional inline SpectroProofer
- Capable of printing on range of media up to 1.5mm thick
- Print speeds of up to 30m² per hour
- ENERGY STAR® qualified



Epson Stylus Pro 4900 with optional inline SpectroProofer

* PANTONE® is the property of Pantone LLC. 98% coverage of PANTONE FORMULA GUIDE solid coated palette based on Epson Proofing Paper White Semimatte printed with Epson printer driver at 2880 x 1440dpi. PANTONE coverage may vary when printed with a third-party RIP.

WHAT'S IN THE BOX

- Epson Stylus Pro 4900
- 11 x 80ml starter ink cartridges
- Power cable
- Software CD
- Set-up guide
- Sample media
- Warranty documents

INK CARTRIDGES*

200ml ink cartridges

● Photo Black	(C13T653100)
● Cyan	(C13T653200)
● Vivid Magenta	(C13T653300)
● Yellow	(C13T653400)
● Light Cyan	(C13T653500)
● Vivid Light Magenta	(C13T653600)
● Light Black	(C13T653700)
● Matte Black	(C13T653800)
● Light Light Black	(C13T653900)
● Orange	(C13T653A00)
● Green	(C13T653B00)

*The Epson Stylus Pro 4900 is supplied with 80ml starter cartridges

FOR THE BEST RESULTS ALWAYS USE GENUINE EPSON INK AND PAPER



myEpsonPrinter.eu

Stay connected and in control of your printer with myEpsonPrinter.eu This web-based solution helps you to manage your fleet of Epson large format printers online. Access up-to-date status and job cost information, receive e-mail notification of issues such as low ink levels and keep your printers at their most productive and cost effective wherever you are. Subscribe to the Epson Return & Recycle program as a myEpsonPrinter.eu member and you can earn additional benefits for returning your empty ink cartridges. For more details please visit www.myEpsonPrinter.eu

PRODUCT SPECIFICATIONS

PRINT TECHNOLOGY Printing method Nozzle configuration Minimum ink droplet volume	Epson Micro Piezo advanced TFP printhead 360 nozzles / 10 channels 3.5pl
PRINT RESOLUTION	2880 x 1440dpi
INK SET	11 colour Epson UltraChrome HDR Ink Pk, Mk, Lk, LLK, C, VM, Lc, VLm, Y, O, G
PRINT SPEED	up to 30m ² per hour
PAPER HANDLING Cut sheet	A2 (17-inch), A3+, A3+, A3, A4, Letter
Print margins sheet media	Mode 1: 3mm (top, sides, bottom); Mode 2: 3mm (top and sides), 14mm (bottom)
Print margins roll media	4 Modes available; Default: 3mm on all edges (top, sides, bottom)
Roll dimensions	203mm – 432mm, (8 inch – 17 inch), A4 – A2+, 2-inch core/ 3-inch core
Edge-to-edge borderless roll media	Max 432mm; 8 inch, 10 inch, 11 inch, 14 inch, 16 inch, 17 inch, 210mm, 254mm, 297mm, 300mm, 329mm, 420mm: 8 inch, 11 inch & 420mm requires spacer
Edge-to-edge borderless cut sheet	Right and left borders; 210mm, 254mm, 297mm, 300mm, 329mm, 356mm, 406mm, 432mm
INK CARTRIDGES*	11 individual 200ml inks Photo Black C13T653100 Light Black C13T653700 Cyan C13T653200 Matte Black C13T653800 Vivid Magenta C13T653300 Light Light Black C13T653900 Yellow C13T653400 Orange C13T653A00 Light Cyan C13T653500 Green C13T653B00 Vivid Light Magenta C13T653600
LIGHT FASTNESS	200 years
CONTROL PANEL	2.5-inch colour LCD with backlight
INTERFACE USB Ethernet TCP/IP	Hi-speed USB – compatible with USB 2.0 specification 100 BASE-TX, 10BASE-T
ELECTRICAL SPECIFICATION Power consumption Power supply	ENERGY STAR® qualified Tier2 compliant Operating: approx 52W. With optional SpectroProofer: approx 55W AC 100 – 240V 50/60Hz
OPERATING SYSTEM	Windows XP/XP 64 bit; Windows Vista 32/64 bit; Windows 7 32/64 bit; Mac OS 10.4.11 or later
MEMORY	Printer 256MB, Network 64MB
DIMENSIONS (WxDxH)	Storage: 863 x 766 x 406mm. Printing: 863 x 1134 x 405mm
WEIGHT	52kg
NOISE LEVEL	45dB (A)
SOFTWARE	Epson Driver with Layout manager Epson NetConfig, Epson Remote Panel, myEpsonPrinter.eu enabled SpectroProofer utilities
WARRANTY	1 year on-site CoverPlus+ as standard Optional CoverPlus+ extension to 3 years available
OPTIONAL SPECTROPROOFER SPECIFICATIONS	
SPECTROPROOFER	ILS20EP/ILS20EPUV
DIMENSIONS (W x H x D)	approx 697 x 179 x 268mm
WEIGHT	approx 10kg (including ILS)
INTERFACE	Connect to printer with dedicated float-in connector
POWER SUPPLY	no cable necessary
MEDIA	8 inch – 17 inch (W) x 10 inch – 600mm (L)
MEASUREMENT AREA	8 – 50 Patches, media: 17 inch – 3 x 2mm (W) x 12mm – 600mm (L)
PATCH SIZE	7 x 12mm
MOUNTER	approx 10kg
BACKING	White/Black, install from rear side of the mounter
CALIBRATION TILE	Install from rear side of the mounter



myEpsonPrinter.eu

For more information please contact

Telephone: 0871 222 6702 (UK)[†]
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740

Web: www.epson.co.uk
www.epson.ie

[†] Calls cost 10 pence per minute from a standard BT landline.
Calls from other networks and mobiles may vary.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®